



## EAGLE mGuard TX/TX

Industrial Networking:Industrial Ethernet:EAGLE System:EAGLE mGuard Firewall

<b>Product description</b>	
Description	Industrial Firewall
Modi	Router, Single Client Transparent (SCT) and Multi Client Transparent(MCT), PPPoE, PPTP
Port type and quantity	Trusted Port: 1 x 10/100BASE-TX, TP-cable, RJ45-socket, autocrossing, autonegotiation, autopolarity Untrusted Port: 1 x 10/100BASE-TX, TP-cable, RJ45-socket, autocrossing, autonegotiation, autopolarity
Type	EAGLE mGuard TX/TX
Order No.	943 011-311
<b>More Interfaces</b>	
Power supply/signaling contact	1 plug-in terminal block, 6-pin
V.24 interface	1 x RJ11 socket
USB interface	1x USB socket
<b>Network size - length of cable</b>	
Twisted pair (TP)	0 - 100 m
<b>Security</b>	
Stateful inspection firewall	firewallrules (incoming/outgoing, modem access, management), IP masquerading, 1-to-1 NAT, ARP limiter, MAC filter optional: ClamAV-Anti-Virus-Engine (HTTP, FTP, POP3, SMTP)
Antivirus protection	
<b>Power requirements</b>	
Operating voltage	9.6 to 60V DC, 18V to 32V AC
Current consumption at 24 V DC	max. 335 mA
<b>Service</b>	
Diagnosics	LEDs (power, link status, data, error, ACA) signaling contact (24 V DC / 1 A), logfile Command Line Interface (CLI), Web-Interface, auto-configuration adapter (ACA21-USB), DHCP, HiDiscovery, Industrial HiVision, SolSoft Policy Server (ISCM), Innominate DeviceManager
Protocols	serial, HTTPS, SSH,SNMP V1/V2/V3, LLDP
Other services	DHCP server/client, DHCP Relay/Option 82, DynDNS, firewall access via V.24 (PPP), NTP, VLAN support (IEEE 802.3pQ), port forwarding
<b>Redundancy</b>	
Redundancy functions	use in redundant net-/ringcoupling, dual homing, router redundancy (VRRP), redundant 24 V power supply
<b>Ambient conditions</b>	
Operating temperature	0 °C to +55 °C
Storage/transport temperature	-40 °C to +80 °C
Relative humidity (non-condensing)	10% to 95%
<b>Mechanical construction</b>	
Dimensions (W x H x D)	47 mm x 131 mm x 111 mm
Mounting	DIN Rail 35 mm
Weight	340 g
Protection class	IP 20
<b>Mechanical stability</b>	

IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13,2 Hz, 90 min.; 0,7g, 13,2 Hz - 100 Hz, 90 min.; 3,5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min

#### **EMC interference immunity**

EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (linie/earth), 1 kV (linie/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)

#### **Approvals**

Safety of industrial control equipment	cUL 508
Hazardous locations	cUL 1604 Class1 Div 2 pending
Germanischer Lloyd	Germanischer Lloyd

#### **Scope of delivery and accessories**

Scope of delivery	device, terminal block, operating instructions, CD-manual
Accessories to order separately	rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, terminal cable, modem cable, HiVision network management, auto-configuration adapter (ACA 11), 19" installation frame