Description

The DV Media Rig is a belt and spring pod supported, multi-adjustment, padded shoulder support compatible with virtually any video camcorder.

Kit Contents

- 1 Dual Stage Adjustable Spring Pod
- 1 Adjustable Velcro™ Belt w/Holster
- 1 21/2 lb. Steel counter-weight
- 1 Velcro[™] Padded shoulder pad *(installed)*
- 1 Aluminum Quick Release camera plate (installed)
- 1 DV Media Rig

Specifications

Weight: 4.5 lbs.

Rig dimensions: 12.5" x 22" x 12"

Pod dimensions: 18" min./32"

Assembly

1. Your new DV Media Rig will require some simple assembly before use. First remove the contents of the package and locate the padded shoulder piece and the camera platform assembly. Lay the handle grip



portion of the rig with the engraving face down.

2. Unscrew the adjustment knob and carefully lay aside the needle bearing and two washers. (fig.1.)





Slide the shoulder portion onto the exposed rod until it is flush against the rig. Place the bearing on the rod and replace the adjustment knob, DO NOT overtighten the knob.

3. Next, slide the weight spacer flange into the center of the counter-weight. Slide the counter-weight and flange onto the exposed bolt, be sure to have the larger diameter portion on top of the weight to avoid unwanted movement of this piece. Tighten the adjustment knob until secure.





4. Loosen the brass screw, lift the silver plunger and remove the camera plate from the quick-release system. Note the position of the anchor screws, by repositioning the



quick-release boot further forward you can adjust the camera balance to your liking. Also note the many camera mounting positions in the QR plate, this versatility should allow for the most comfortable and balanced operation of any camera.



5. Insert the base of the support pod through the plastic d-clip and into the holster. Compress the rod to a minimum length and tighten the adjustment knobs.

6. With your hand, guide the narrow brass tip into the flexible spring cup located on the bottom of the rig. Loosen the tension knobs on the rod, this



will engage the spring pod with the weight of the rig , dampening movement and negating camera shake. These knobs can be adjusted independently for a variable amount of dampening.

7. Congratulations! You are ready to use your new DV MediaRig. At this point you may wish to make some adjustments for the best balance and comfort. We suggest begininning with the QR plate and the shoulder joint adjustments, these portions establish a good foundation for balance. After the QR plate and shoulder joint are set, move on to some minor adjustments of the counter-weight and spring pod tension. Most adjustments can be made while wearing the rig, so you can quickly adjust and keep shooting!

Thanks for purchasing the DV Media Rig and Good Luck!

This product is covered by VariZoom's two year manufacturers warranty covering any defects or missing parts. All additional or replacement parts will incur an additional cost.