

PD-SATA 400+



















The Pleiades (PD-SATA 400+), a slim, stylish and powerful aluminum enclosure for your 3.5" SATA hard drive. Features fanless design and passive cooling, ideal for multi-media users and quiet working environments.



| Model No. | PD-FR4U2OS |
|----------------|---|
| Bridge Chipset | Oxford 934SSA |
| Case Material | High quality aluminium with internal metal chassis for optimised heat dissipation |

| Application | 3.5" SATA-I or SATA-II Hard Drive (1.5Gb/s or 3.0Gb/s) |
|---------------------------|---|
| Interface/Ports | FireWire 400 (1394a) 2 ports USB 2.0 High Speed (USB1.1 compatible) 1 port |
| Data Transfer | Firewire 400 (1394a) up to 400Mbps (50MB/s) USB 2.0 up to 480Mbps (60MB/s) USB 1.1 up to 12Mbps (1.5MB/s) |
| System Requirements (PC) | Firewire 400: Windows 2000/XP/Vista USB 2.0: Windows 2000/XP/Vista Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card) |
| System Requirements (Mac) | Firewire 400: Mac OS 10.1.5 or later USB 2.0: Mac OS 10.2 or later Your hardware device must have the correct corresponding port (eg. USB 2.0, USB 1.1 or PCI card) |
| Power Supply | External power adapter universal auto-switching (UL, cUL, CE, TUV approved) Input: AC 100-240V, 1.2A, 50-60Hz Output: DC +12V/2A, +5V/2A |
| Product Size | 22.7cm x 13.7cm x 3.5cm |
| Packing Accessories | PD-SATA 400+ enclosure (no HDD included) USB 2.0 cable (4pin to 4pin) Firewire 400 cable (6pin to 6pin) Power adapter plus cord Manual |
| Carton/Packing | Retail Box Size: 32cm x 24cm x 10.5cm Carton Size: 56.5cm x 51cm x 35cm (10pcs per carton) G.W. 16.5kg |
| Remarks | |